TITLE: Product Standard - Hardware - Air Hose and Accessories PAGE: 1 of 2

Bluestem Brands Product Standard

Product Family Home Improvement

Product Dept Hardware

Product Group(s) Air Hose and Accessories

| Vendor Responsibility | All BSB vendors are responsible to execute the following: Follow all required BSB Quality Assurance processes. Manufacture products responsibly in safe and socially compliant factories. Implement and maintain safety, quality assurance and good manufacturing processes to ensure that raw materials, components and finished products meet requirements throughout the product life cycle. Verify that safe, quality products are shipped to BSB and comply with all applicable state and federal laws and regulations of the USA and are in conformance with the BSB purchase order terms and conditions. |
|--------------------------|---|
| | In addition to this product standard: • Follow BSB merchandising's design and costing direction when choosing materials, construction and performance attributes. • Products must pass product testing per the appropriate BSB test protocols at a BSB approved third party lab Vendors should request advance copies of test protocols from the third party testing lab as a supplement to this standard. |
| | Any deviations to the requirements listed in the standard must be approved by BSB Buyer and/or BSB Quality Assurance. |
| General Requirements | |

| | Good | Better | Best |
|---|---------|---|---|
| Body Material PVC | | Recoil PVC/Rubber (Hybrid) | Rubber |
| Hose Diameter | 3/8" | 3/8" | 3/8" |
| Accepts fitting size | 1/4" | 1/4" | 1/4" |
| Hose Length | 25 feet | 25 feet | 25 feet |
| Max PSI delivers 300-PSI for maximum working pressure | | delivers 300-PSI for maximum working pressure | delivers 300-PSI for maximum working pressure |



TITLE: Product Standard – Hardware – Air Hose and Accessories PAGE: 2 of 2

| Features | Kink-resistant Oil- and abrasion-resistant Includes bend restrictors | Kink-resistant Oil- and abrasion-resistant Includes bend restrictors | Service temperature range: -20° to +165° F Oil and abrasion-resistant Resists twisting for increased life |
|-------------|--|--|---|
| Accessories | | Hard Shell Case 5 male couples 1 quick connect coupler Pipe thread tape | |

| | DOCUMENT REVISION HISTORY | | | | | | | |
|-----|---------------------------|---------------|----------|---------------|--|--|--|--|
| REV | REV DATE | PREPARER | APPROVER | DESCRIPTION | | | | |
| 01 | | Nancy Bartsch | | Initial draft | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |