

Bluestem Brands Product Standard

| Product Family | Home Improvement | | | | | |
|--------------------------|---|--------------------|------|--|--|--|
| Product Dept | Hardware | | | | | |
| Product Group(s) | Air Tool Brad Nailer | | | | | |
| Vendor Responsibility | All BSB vendors are responsible to execute the following: Follow all required BSB Quality Assurance processes. Manufacture products responsibly in safe and socially compliant factories. Implement and maintain safety, quality assurance and good manufacturing processes to ensure that raw materials, components and finished products meet requirements throughout the product life cycle. Verify that safe, quality products are shipped to BSB and comply with all applicable state and federal laws and regulations of the USA and are in conformance with the BSB purchase order terms and conditions. | | | | | |
| | In addition to this product standard: Follow BSB merchandising's design and costing direction when choosing materials, construction and performance attributes. Products must pass product testing per the appropriate BSB test protocols at a BSB approved third party lab Vendors should request advance copies of test protocols from the third party testing lab as a supplement to this standard. Any deviations to the requirements listed in the standard must be approved by BSB Buyer and/or BSB Quality Assurance. | | | | | |
| General Requirements | | | | | | |
| | Occul | Detter | Deet | | | |
| | Good | Better | Best | | | |
| Body Material | Magnesium | Aluminum | | | | |
| Nail Gauge | 18 | 18 | | | | |
| Air Pressure | 60-100 | 60 -100 | | | | |
| Magazine Capacity | 100 | 100 | | | | |
| Maximum Nail Length | 3/8-in to 2-in | 3/8-in to 2 1/8-in | | | | |



TITLE: Product Standard – Hardware – Air Tool Brad Nailer PAGE: 2 of 2

| Strip or Coil | Strip | Strip | |
|--|---|--|--|
| Minimum Recommended Air Delivery SCFM @ 90PSI | 1.3 SCFM @ 90 psi?? | 2.6 SCFM @ 90 psi?/ | |
| Features | The magazine window shows remaining brad count Quick release for clearing jams | Tool-free nose latch for quick jam clearing Tool-free depth adjustment Indicator that nails are running low or dry fire prevention | |
| Accessories | | | |
| | | | |

| | DOCUMENT REVISION HISTORY | | | | | | |
|-----|---------------------------|---------------|----------|---------------|--|--|--|
| REV | REV DATE | PREPARER | APPROVER | DESCRIPTION | | | |
| 01 | | Nancy Bartsch | | Initial draft | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |